



Dash & Thread Sizes

FJX

BSP/NPT

-2 - 1/8"

-4 - 1/4"

-6 - 3/8"

-8 - 1/2"

-12 - 3/4"

-16 - 1"

-20 - 1 1/4"

-24 - 1 1/2"

-32 - 2"

BSPP
(Parallel)
Has a 60
Degree
Cone.

NPT is
always
Tapered.

BSPP



JIC/SAE(ORB)

-3 - 3/8"

-4 - 7/16"

-5 - 1/2"

-6 - 9/16"

-8 - 3/4"

-10 - 7/8"

-12 - 1 1/16"

-14 - 1 3/16"

-16 - 1 5/16"

-20 - 1 5/8"

-24 - 1 7/8"

-32 - 2 1/2"

-48 - 3 1/2"

Jic has a 37
Degree Cone.

SAE is parallel
with an
O'Ring at the
bottom of the
thread
(against the
hex)

JIC



SAE (ORB)



FFORX

SAE (ORFS)

-4 - 9/16"

-6 - 11/16"

-8 - 13/16"

-10 - 1"

-12 - 1 3/16"

-16 - 1 7/16"

-20 - 1 11/16"

ORFS has an
O'Ring on the
face (O'Ring
Face Seal)

ORFS



Scan the QR code to view
the Gates Crimper
S.T.A.M.P.E.D
instructions.



Dash & Thread Sizes

FDLORX

L Series

6L – M12x1.5
8L – M14x1.5
10L – M16x1.5
12L – M18x1.5
15L – M22x1.5
18L – M26x1.5
22L – M30x2
28L – M36x2
35L – M45x2
42L – M52x2

Number refers to the outer diameter of the tip of the standpipe in millimetres. Seals with a 24 degree cone.

Light Series (L)



FDHORX

S Series

6S – M14x1.5
8S – M16x1.5
10S – M18x1.5
12S – M20x1.5
14S – M22x1.5
16S – M24x1.5
20S – M30x2
25S – M36x2
30S – M42x2
38S – M52x2

Number refers to the outer diameter of the tip of the standpipe in millimetres. Seals with a 24 degree cone.

Heavy Series (S)



Scan the QR code to view
the Gates Crimper
Training Manual

Flotec Industrial Limited

Unit 8, Jubilee Drive, Off Pavilion Way, Loughborough, Leicestershire LE11 5GW

Tel: +44 (0) 1509 230 100 Email: sales@flocconline.com

Web: <https://www.flotecindustrial.co.uk> Online Store: <https://www.flocconline.com>